

MYERS HR SERIES SHALLOW WELL JET

SHALLOW WELL HR SELECTION TABLE

Cat. No.	Motor HP	Discharge Pressure in Lbs.	Capacity in U.S. Gallons per Minute Suction Lift in Feet			Shut-Off PSI
			5	15	25	
HR50S	1/2	20	11.5	9	6	70
		30	11.5	9	6	
		40	10.5	7.5	5	
		50	5.5	3.5	2	

MYERS QD SERIES SHALLOW WELL JET

SHALLOW WELL QUICK DRAW SELECTION TABLE

Cat. No.	Motor HP	Discharge Pressure in Lbs.	Capacity in U.S. Gallons per Minute Suction Lift in Feet						Shut-Off PSI
			0	5	10	15	20	25	
QD50S	1/2	20	12.5	11.5	10.5	9	7.5	6	65
		30	11	10	9.5	8	6.5	5	
		40	9	8	7.5	6	4.5	3	
		50	6.5	5.5	5	4	3	2	
QD75S	3/4	20	20	18	16.5	15	13	10	65
		30	19	17	15.5	14	12	9	
		40	16	14.5	12	11	9	8	
		50	9.5	8.5	7.5	6.5	4.5	3.5	
QD100S	1	20	26.5	24	22	19	16	13	62
		30	25	23	21	18	15	11	
		40	20	18.5	16	13	10.5	7	
		50	12.5	11	9.5	7	5		



MYERS HJ SERIES SHALLOW WELL JET

SHALLOW WELL HJ SELECTION TABLE

Cat. No.	Motor HP	Discharge Pressure in Lbs.	Capacity in U.S. Gallons per Minute Suction Lift in Feet			Shut-Off PSI
			5	15	25	
HJ50S*	1/2	20	14.5	11.5	7	65
		30	14.5	11.5	7	
		40	10	8	6	
		50	5.5	3.5	2	
HJ75S*	3/4	20	23.5	17.5	10.5	69
		30	23.5	17.5	10.5	
		40	19.5	16.5	10.5	
		50	12.5	9	5	
HJ100S*	1	20	27.5	21	13	67
		30	27.5	21	13	
		40	25.5	21	13	
		50	19	15.5	12	